

*Advance Information*

AN1812/D  
Rev. 1, 12/2001

Common Footprint for the  
MPC750, MPC755,  
MPC7400, and MPC7410

*CPD Applications*

This document describes how to design a platform with a common footprint for the MPC750, MPC755, MPC7400, and MPC7410; that is, it is intended to help design a single board compatible with all of these devices. Although this document contains relevant information, it is not intended to be a complete migration guide for moving from G3- to G4-class systems.

As a general note, refer to the appropriate hardware specifications and user's manual for the specific device under consideration.

For this document, the following system definition is assumed for the MPC750, MPC755, MPC7400 and MPC7410:

- 64-bit data bus mode
- No data retry
- Bus operates in 60x mode

Note that all the CPUs can run in 60x bus, and the MPC7400 and MPC7410 have the ability to run in an enhanced mode MPX.



## 1.1 Main Pin Difference

This section includes Table 1 which lists the main differences between the MPC750, MPC755, MPC7400 and MPC7410 and the configuration pins. The MPX bus column provides information for designers to take advantage of the MPX bus mode for future board revisions.

**Table 1. Main Pin Difference and Configuration Pins**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x Bus	MPC7400/ MPC7410 MPX Bus	Comment
B3	I/O	No Connect	No Connect	SHD[0]	SHD[0]	Pull-up (in multi CPU system, connect together) <sup>1</sup>
B4	I/O	No Connect	No Connect	SHD[1]	SHD[1]	Pull-up (in multi CPU system, connect together) <sup>1</sup>
B5	Output	No Connect	No Connect	No Function	HIT	Pull-up to OVDD <sup>1</sup>
K9	Output	No Connect	No Connect	No Function	DRDY	
K19	Output	No Connect	No Connect	L2A17	L2A17	Connect to L2 SRAM. A pull-up to L2VODD should be used if MPC750/MPC755 1Mbyte compatibility is required when using 2Mbytes of SRAM.
W19	Output	No Connect	No Connect	L2A18	L2A18	Reserved for future expansion
A4	Input	PLL_CFG[0]	PLL_CFG[0]	PLL_CFG[0]	PLL_CFG[0]	See hardware specification document. Should put in a pull up/down pair for each to allow any configuration.
A5	Input	PLL_CFG[1]	PLL_CFG[1]	PLL_CFG[1]	PLL_CFG[1]	
A6	Input	PLL_CFG[2]	PLL_CFG[2]	PLL_CFG[2]	PLL_CFG[2]	
A7	Input	PLL_CFG[3]	PLL_CFG[3]	PLL_CFG[3]	PLL_CFG[3]	
F9	Input	LSSD_MODE	LSSD_MODE	LSSD_MODE	LSSD_MODE	Pull-up to OVDD
F7	Input	L2_TSTCLK	L2_TSTCLK	L2_TSTCLK	L2_TSTCLK	
F8	Input	L1_TSTCLK	L1_TSTCLK	L1_TSTCLK	L1_TSTCLK	
K11	Input	No Connect	No Connect	CHK	CHK	
K13		VOLDET	VOLDET	L2OVDD[13]	L2OVDD[13]	Must be connected to L2OVDD
L7	I/O or Output	ABB	ABB	ABB	ABB	Pull-up to OVDD <sup>1</sup>
C2	I/O or Output	CI	CI	CI	CI	
C3	I/O or Output	WT	WT	WT	WT	
K5	I/O or Output	DBB	DBB	DBB	DBB	
D1	Input	DBWO	DBWO	DBWO	DTI[0] <sup>2</sup>	
H6	Input	DRTRY	DRTRY	No Function	DTI[1] <sup>2</sup>	Connect to HRESET for no Data retry mode in 60x bus.

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

**Table 1. Main Pin Difference and Configuration Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x Bus	MPC7400/ MPC7410 MPX Bus	Comment
G1	Input	DBDIS	DBDIS	No Function	DTI[2] <sup>2</sup>	Pull-up to OVDD <sup>1</sup>
A3	Input	TLBISYNC	TLBISYNC	EMODE	EMODE	Pull-up to OVDD (64-bit 60x bus)
W1		No Connect	BVSEL	BVSEL	BVSEL	See Table 2 and Table 3 for voltages.
A19		No Connect	L2VSEL	L2VSEL	L2VSEL	

<sup>1</sup> See the individual hardware specifications document for the recommended resistor value.

<sup>2</sup> DTI[0:2] should be pulled low in MPX bus mode to disable re-ordering.

## 1.2 I/O Voltage Selection

This section lists the four footprint power planes and displays the section matrix for the I/O voltages.

In addition, the footprint should have four power planes:

- Ground
- The CPU core voltage, [VDD]
- The I/O voltage for the system bus, [OVDD]
- The I/O voltage for the L2 SRAM interface, [L2OVDD]

The I/O voltages [OVDD and L2OVDD] are selectable on all the CPUs except the MPC750, which supports 3.3V only on both of these interfaces.

Table 2 and Table 3 show the selection matrix for the I/O voltages:

**Table 2. I/O Voltage Selection—BVSEL**

BVSEL	MPC750	MPC755	MPC7400	MPC7410 (Rev E)
0	N/A	N/A	1.8V	1.8V
HRESET	N/A	N/A	N/A	2.5V
1	N/A	OVDD (2.5V/3.3V)	3.3V	3.3V
-HRESET	N/A	N/A	N/A	3.3V
Unconnected (internal pull-up)	N/A	2.5V/3.3V	3.3V	3.3V



**Table 3. I/O Voltage Selection—L2VSEL**

L2VSEL	MPC750	MPC755	MPC7400	MPC7410 (Rev E)
0	N/A	N/A	1.8V	1.8V
HRESET	N/A	N/A	2.5V	2.5V
1	N/A	L2VDD (2.5V/3.3V)	3.3V	2.5V
~HRESET	N/A	N/A	N/A	N/A
Unconnected (internal pull-up)	N/A	2.5V/3.3V	3.3V	2.5V

Table 4 pertains to the remaining pins, and the comments are valid for the common footprint.

**Table 4. Remaining Pins**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
A13	I/O	A[00]	A[00]	A[00]	
D2	I/O	A[01]	A[01]	A[01]	
H11	I/O	A[02]	A[02]	A[02]	
C1	I/O	A[03]	A[03]	A[03]	
B13	I/O	A[04]	A[04]	A[04]	
F2	I/O	A[05]	A[05]	A[05]	
C13	I/O	A[06]	A[06]	A[06]	
E5	I/O	A[07]	A[07]	A[07]	
D13	I/O	A[08]	A[08]	A[08]	
G7	I/O	A[09]	A[09]	A[09]	
F12	I/O	A[10]	A[10]	A[10]	
G3	I/O	A[11]	A[11]	A[11]	
G6	I/O	A[12]	A[12]	A[12]	
H2	I/O	A[13]	A[13]	A[13]	
E2	I/O	A[14]	A[14]	A[14]	
L3	I/O	A[15]	A[15]	A[15]	
G5	I/O	A[16]	A[16]	A[16]	
L4	I/O	A[17]	A[17]	A[17]	
G4	I/O	A[18]	A[18]	A[18]	
J4	I/O	A[19]	A[19]	A[19]	
H7	I/O	A[20]	A[20]	A[20]	
E1	I/O	A[21]	A[21]	A[21]	
G2	I/O	A[22]	A[22]	A[22]	
F3	I/O	A[23]	A[23]	A[23]	

**Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410**

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
J7	I/O	A[24]	A[24]	A[24]	
M3	I/O	A[25]	A[25]	A[25]	
H3	I/O	A[26]	A[26]	A[26]	
J2	I/O	A[27]	A[27]	A[27]	
J6	I/O	A[28]	A[28]	A[28]	
K3	I/O	A[29]	A[29]	A[29]	
K2	I/O	A[30]	A[30]	A[30]	
L2	I/O	A[31]	A[31]	A[31]	
N3	Input	$\overline{\text{AACK}}$	$\overline{\text{AACK}}$	$\overline{\text{AACK}}$	Pull up to OVDD <sup>1</sup>
C4	I/O	AP[0]	AP[0]	AP[0]	Pulled up to OVDD if not used to reduce noise and power.
C5	I/O	AP[1]	AP[1]	AP[1]	
C6	I/O	AP[2]	AP[2]	AP[2]	
C7	I/O	AP[3]	AP[3]	AP[3]	
L6	I/O	$\overline{\text{ARTRY}}$	$\overline{\text{ARTRY}}$	$\overline{\text{ARTRY}}$	Pull up to OVDD <sup>1</sup>
A8		AVDD	AVDD	AVDD	Use filter circuit <sup>2</sup>
H1	Input	$\overline{\text{BG}}$	$\overline{\text{BG}}$	$\overline{\text{BG}}$	Pull down if no other master.
E7	Output	$\overline{\text{BR}}$	$\overline{\text{BR}}$	$\overline{\text{BR}}$	
C2	Output	$\overline{\text{CI}}$	$\overline{\text{CI}}$	$\overline{\text{CI}}$	
B8	Input	$\overline{\text{CKSTP\_IN}}$	$\overline{\text{CKSTP\_IN}}$	$\overline{\text{CKSTP\_IN}}$	Pull up to OVDD <sup>1</sup>
D7	Output	$\overline{\text{CKSTP\_OUT}}$	$\overline{\text{CKSTP\_OUT}}$	$\overline{\text{CKSTP\_OUT}}$	
E3	Output	CLKOUT	CLKOUT	CLKOUT	
W12	I/O	DH[00]	DH[00]	D[00]	
W11	I/O	DH[01]	DH[01]	D[01]	
V11	I/O	DH[02]	DH[02]	D[02]	
T9	I/O	DH[03]	DH[03]	D[03]	
W10	I/O	DH[04]	DH[04]	D[04]	
U9	I/O	DH[05]	DH[05]	D[05]	
U10	I/O	DH[06]	DH[06]	D[06]	
M11	I/O	DH[07]	DH[07]	D[07]	
M9	I/O	DH[08]	DH[08]	D[08]	
P8	I/O	DH[09]	DH[09]	D[09]	
W7	I/O	DH[10]	DH[10]	D[10]	
P9	I/O	DH[11]	DH[11]	D[11]	
W9	I/O	DH[12]	DH[12]	D[12]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**



**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
R10	I/O	DH[13]	DH[13]	D[13]	
W6	I/O	DH[14]	DH[14]	D[14]	
V7	I/O	DH[15]	DH[15]	D[15]	
V6	I/O	DH[16]	DH[16]	D[16]	
U8	I/O	DH[17]	DH[17]	D[17]	
V9	I/O	DH[18]	DH[18]	D[18]	
T7	I/O	DH[19]	DH[19]	D[19]	
U7	I/O	DH[20]	DH[20]	D[20]	
R7	I/O	DH[21]	DH[21]	D[21]	
U6	I/O	DH[22]	DH[22]	D[22]	
W5	I/O	DH[23]	DH[23]	D[23]	
U5	I/O	DH[24]	DH[24]	D[24]	
W4	I/O	DH[25]	DH[25]	D[25]	
P7	I/O	DH[26]	DH[26]	D[26]	
V5	I/O	DH[27]	DH[27]	D[27]	
V4	I/O	DH[28]	DH[28]	D[28]	
W3	I/O	DH[29]	DH[29]	D[29]	
U4	I/O	DH[30]	DH[30]	D[30]	
R5	I/O	DH[31]	DH[31]	D[31]	
M6	I/O	DL[00]	DL[00]	D[32]	
P3	I/O	DL[01]	DL[01]	D[33]	
N4	I/O	DL[02]	DL[02]	D[34]	
N5	I/O	DL[03]	DL[03]	D[35]	
R3	I/O	DL[04]	DL[04]	D[36]	
M7	I/O	DL[05]	DL[05]	D[37]	
T2	I/O	DL[06]	DL[06]	D[38]	
N6	I/O	DL[07]	DL[07]	D[39]	
U2	I/O	DL[08]	DL[08]	D[40]	
N7	I/O	DL[09]	DL[09]	D[41]	
P11	I/O	DL[10]	DL[10]	D[42]	
V13	I/O	DL[11]	DL[11]	D[43]	
U12	I/O	DL[12]	DL[12]	D[44]	
P12	I/O	DL[13]	DL[13]	D[45]	
T13	I/O	DL[14]	DL[14]	D[46]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
W13	I/O	DL[15]	DL[15]	D[47]	
U13	I/O	DL[16]	DL[16]	D[48]	
V10	I/O	DL[17]	DL[17]	D[49]	
W8	I/O	DL[18]	DL[18]	D[50]	
T11	I/O	DL[19]	DL[19]	D[51]	
U11	I/O	DL[20]	DL[20]	D[52]	
V12	I/O	DL[21]	DL[21]	D[53]	
V8	I/O	DL[22]	DL[22]	D[54]	
TU1	I/O	DL[23]	DL[23]	D[55]	
P1	I/O	DL[24]	DL[24]	D[56]	
V1	I/O	DL[25]	DL[25]	D[57]	
U1	I/O	DL[26]	DL[26]	D[58]	
N1	I/O	DL[27]	DL[27]	D[59]	
R2	I/O	DL[28]	DL[28]	D[60]	
V3	I/O	DL[29]	DL[29]	D[61]	
U3	I/O	DL[30]	DL[30]	D[62]	
W2	I/O	DL[31]	DL[31]	D[63]	
K1	Input	$\overline{\text{DBG}}$	DBG	$\overline{\text{DBG}}$	Pull down if no other masters
L1	I/O	DP[0]	DP[0]	DP[0]	Pulled up if not used to reduce noise and power.
P2	I/O	DP[1]	DP[1]	DP[1]	
M2	I/O	DP[2]	DP[2]	DP[2]	
V2	I/O	DP[3]	DP[3]	DP[3]	
M1	I/O	DP[4]	DP[4]	DP[4]	
N2	I/O	DP[5]	DP[5]	DP[5]	
T3	I/O	DP[6]	DP[6]	DP[6]	
R1	I/O	DP[7]	DP[7]	DP[7]	
B1	I/O	$\overline{\text{GBL}}$	$\overline{\text{GBL}}$	$\overline{\text{GBL}}$	Pull up <sup>1</sup>
D10		GND[01]	GND[01]	GND[01]	Ground for the device
D14		GND[02]	GND[02]	GND[02]	
D16		GND[03]	GND[03]	GND[03]	
D4		GND[04]	GND[04]	GND[04]	
D6		GND[05]	GND[05]	GND[05]	
E12		GND[06]	GND[06]	GND[06]	
E8		GND[07]	GND[07]	GND[07]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**



Table 4. Remaining Pins (continued)

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
F4		GND[08]	GND[08]	GND[08]	
F6		GND[09]	GND[09]	GND[09]	
F10		GND[10]	GND[10]	GND[10]	
F14		GND[11]	GND[11]	GND[11]	
F16		GND[12]	GND[12]	GND[12]	
G9		GND[13]	GND[13]	GND[13]	
G11		GND[14]	GND[14]	GND[14]	
H5		GND[15]	GND[15]	GND[15]	
H8		GND[16]	GND[16]	GND[16]	
H10		GND[17]	GND[17]	GND[17]	
H12		GND[18]	GND[18]	GND[18]	
H15		GND[19]	GND[19]	GND[19]	
J9		GND[20]	GND[20]	GND[20]	
J11		GND[21]	GND[21]	GND[21]	
K4		GND[22]	GND[22]	GND[22]	
K6		GND[23]	GND[23]	GND[23]	
K8		GND[24]	GND[24]	GND[24]	
K10		GND[25]	GND[25]	GND[25]	
K12		GND[26]	GND[26]	GND[26]	
K14		GND[27]	GND[27]	GND[27]	
K16		GND[28]	GND[28]	GND[28]	
L9		GND[29]	GND[29]	GND[29]	
L11		GND[30]	GND[30]	GND[30]	
M5		GND[31]	GND[31]	GND[31]	
M8		GND[32]	GND[32]	GND[32]	
M10		GND[33]	GND[33]	GND[33]	
M12		GND[34]	GND[34]	GND[34]	
M15		GND[35]	GND[35]	GND[35]	
N9		GND[36]	GND[36]	GND[36]	
N11		GND[37]	GND[37]	GND[37]	
P4		GND[38]	GND[38]	GND[38]	
P6		GND[39]	GND[39]	GND[39]	
P10		GND[40]	GND[40]	GND[40]	
P14		GND[41]	GND[41]	GND[41]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)



**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
P16		GND[42]	GND[42]	GND[42]	
R8		GND[43]	GND[43]	GND[43]	
R12		GND[44]	GND[44]	GND[44]	
T4		GND[45]	GND[45]	GND[45]	
T6		GND[46]	GND[46]	GND[46]	
T10		GND[47]	GND[47]	GND[47]	
T14		GND[48]	GND[48]	GND[48]	
T16		GND[49]	GND[49]	GND[49]	
B6	Input	HRESET	HRESET	HRESET	Driven constantly from reset controller
C11	Input	INT	INT	INT	Pull up if not driven constantly
L17	Output	L2ADDR[0]	L2ADDR[0]	L2A[00]	
L18	Output	L2ADDR[1]	L2ADDR[1]	L2A[01]	
L19	Output	L2ADDR[2]	L2ADDR[2]	L2A[02]	
M19	Output	L2ADDR[3]	L2ADDR[3]	L2A[03]	
K18	Output	L2ADDR[4]	L2ADDR[4]	L2A[04]	
K17	Output	L2ADDR[5]	L2ADDR[5]	L2A[05]	
K15	Output	L2ADDR[6]	L2ADDR[6]	L2A[06]	
J19	Output	L2ADDR[7]	L2ADDR[7]	L2A[07]	
J18	Output	L2ADDR[8]	L2ADDR[8]	L2A[08]	
J17	Output	L2ADDR[9]	L2ADDR[9]	L2A[09]	
J16	Output	L2ADDR[10]	L2ADDR[10]	L2A[10]	
H18	Output	L2ADDR[11]	L2ADDR[11]	L2A[11]	
H17	Output	L2ADDR[12]	L2ADDR[12]	L2A[12]	
J14	Output	L2ADDR[13]	L2ADDR[13]	L2A[13]	
J13	Output	L2ADDR[14]	L2ADDR[14]	L2A[14]	
H19	Output	L2ADDR[15]	L2ADDR[15]	L2A[15]	
G18	Output	L2ADDR[16]	L2ADDR[16]	L2A[16]	
L13		L2AVDD	L2AVDD	L2AVDD	Use filter circuit <sup>2</sup>
P17	Output	L2CE	L2CE	L2CE	
N15	Output	L2CLKOUTA	L2CLKOUTA	L2CLKOUTA	
L16	Output	L2CLKOUTB	L2CLKOUTB	L2CLKOUTB	
U14	I/O	L2DATA[0]	L2DATA[0]	L2D[00]	
R13	I/O	L2DATA[1]	L2DATA[1]	L2D[01]	
W14	I/O	L2DATA[2]	L2DATA[2]	L2D[02]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**



**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
W15	I/O	L2DATA[3]	L2DATA[3]	L2D[03]	
V15	I/O	L2DATA[4]	L2DATA[4]	L2D[04]	
U15	I/O	L2DATA[5]	L2DATA[5]	L2D[05]	
W16	I/O	L2DATA[6]	L2DATA[6]	L2D[06]	
V16	I/O	L2DATA[7]	L2DATA[7]	L2D[07]	
W17	I/O	L2DATA[8]	L2DATA[8]	L2D[08]	
V17	I/O	L2DATA[9]	L2DATA[9]	L2D[09]	
U17	I/O	L2DATA[10]	L2DATA[10]	L2D[10]	
W18	I/O	L2DATA[11]	L2DATA[11]	L2D[11]	
V18	I/O	L2DATA[12]	L2DATA[12]	L2D[12]	
U18	I/O	L2DATA[13]	L2DATA[13]	L2D[13]	
V19	I/O	L2DATA[14]	L2DATA[14]	L2D[14]	
U19	I/O	L2DATA[15]	L2DATA[15]	L2D[15]	
T18	I/O	L2DATA[16]	L2DATA[16]	L2D[16]	
T17	I/O	L2DATA[17]	L2DATA[17]	L2D[17]	
R19	I/O	L2DATA[18]	L2DATA[18]	L2D[18]	
R18	I/O	L2DATA[19]	L2DATA[19]	L2D[19]	
R17	I/O	L2DATA[20]	L2DATA[20]	L2D[20]	
R15	I/O	L2DATA[21]	L2DATA[21]	L2D[21]	
P19	I/O	L2DATA[22]	L2DATA[22]	L2D[22]	
P18	I/O	L2DATA[23]	L2DATA[23]	L2D[23]	
P13	I/O	L2DATA[24]	L2DATA[24]	L2D[24]	
N14	I/O	L2DATA[25]	L2DATA[25]	L2D[25]	
N13	I/O	L2DATA[26]	L2DATA[26]	L2D[26]	
N19	I/O	L2DATA[27]	L2DATA[27]	L2D[27]	
N17	I/O	L2DATA[28]	L2DATA[28]	L2D[28]	
M17	I/O	L2DATA[29]	L2DATA[29]	L2D[29]	
M13	I/O	L2DATA[30]	L2DATA[30]	L2D[30]	
M18	I/O	L2DATA[31]	L2DATA[31]	L2D[31]	
H13	I/O	L2DATA[32]	L2DATA[32]	L2D[32]	
G19	I/O	L2DATA[33]	L2DATA[33]	L2D[33]	
G16	I/O	L2DATA[34]	L2DATA[34]	L2D[34]	
G15	I/O	L2DATA[35]	L2DATA[35]	L2D[35]	
G14	I/O	L2DATA[36]	L2DATA[36]	L2D[36]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
G13	I/O	L2DATA[37]	L2DATA[37]	L2D[37]	
F19	I/O	L2DATA[38]	L2DATA[38]	L2D[38]	
F18	I/O	L2DATA[39]	L2DATA[39]	L2D[39]	
F13	I/O	L2DATA[40]	L2DATA[40]	L2D[40]	
E19	I/O	L2DATA[41]	L2DATA[41]	L2D[41]	
E18	I/O	L2DATA[42]	L2DATA[42]	L2D[42]	
E17	I/O	L2DATA[43]	L2DATA[43]	L2D[43]	
E15	I/O	L2DATA[44]	L2DATA[44]	L2D[44]	
D19	I/O	L2DATA[45]	L2DATA[45]	L2D[45]	
D18	I/O	L2DATA[46]	L2DATA[46]	L2D[46]	
D17	I/O	L2DATA[47]	L2DATA[47]	L2D[47]	
C18	I/O	L2DATA[48]	L2DATA[48]	L2D[48]	
C17	I/O	L2DATA[49]	L2DATA[49]	L2D[49]	
B19	I/O	L2DATA[50]	L2DATA[50]	L2D[50]	
B18	I/O	L2DATA[51]	L2DATA[51]	L2D[51]	
B17	I/O	L2DATA[52]	L2DATA[52]	L2D[52]	
A18	I/O	L2DATA[53]	L2DATA[53]	L2D[53]	
A17	I/O	L2DATA[54]	L2DATA[54]	L2D[54]	
A16	I/O	L2DATA[55]	L2DATA[55]	L2D[55]	
B16	I/O	L2DATA[56]	L2DATA[56]	L2D[56]	
C16	I/O	L2DATA[57]	L2DATA[57]	L2D[57]	
A14	I/O	L2DATA[58]	L2DATA[58]	L2D[58]	
A15	I/O	L2DATA[59]	L2DATA[59]	L2D[59]	
C15	I/O	L2DATA[60]	L2DATA[60]	L2D[60]	
B14	I/O	L2DATA[61]	L2DATA[61]	L2D[61]	
C14	I/O	L2DATA[62]	L2DATA[62]	L2D[62]	
E13	I/O	L2DATA[63]	L2DATA[63]	L2D[63]	
V14	I/O	L2DP[0]	L2DP[0]	L2DP[0]	
U16	I/O	L2DP[1]	L2DP[1]	L2DP[1]	
T19	I/O	L2DP[2]	L2DP[2]	L2DP[2]	
N18	I/O	L2DP[3]	L2DP[3]	L2DP[3]	
H14	I/O	L2DP[4]	L2DP[4]	L2DP[4]	
F17	I/O	L2DP[5]	L2DP[5]	L2DP[5]	
C19	I/O	L2DP[6]	L2DP[6]	L2DP[6]	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

Table 4. Remaining Pins (continued)

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
B15	I/O	L2DP[7]	L2DP[7]	L2DP[7]	
D15		L2OVDD[01]	L2OVDD[01]	L2OVDD[01]	Level 2 cache I/O voltage
E14		L2OVDD[02]	L2OVDD[02]	L2OVDD[02]	
E16		L2OVDD[03]	L2OVDD[03]	L2OVDD[03]	
H16		L2OVDD[04]	L2OVDD[04]	L2OVDD[04]	
J15		L2OVDD[05]	L2OVDD[05]	L2OVDD[05]	
L15		L2OVDD[06]	L2OVDD[06]	L2OVDD[06]	
M16		L2OVDD[07]	L2OVDD[07]	L2OVDD[07]	
P15		L2OVDD[08]	L2OVDD[08]	L2OVDD[08]	
R14		L2OVDD[09]	L2OVDD[09]	L2OVDD[09]	
R16		L2OVDD[10]	L2OVDD[10]	L2OVDD[10]	
T15		L2OVDD[11]	L2OVDD[11]	L2OVDD[11]	
F15		L2OVDD[12]	L2OVDD[12]	L2OVDD[12]	
L14	Input	L2SYNC_IN	L2SYNC_IN	L2SYNC_IN	
M14	Output	L2SYNC_OUT	L2SYNC_OUT	L2SYNC_OUT	Connected to L2SYNC_IN with a trace length equal to the address and data for L2 SRAMs
N16		L2WE	L2WE	L2WE	
G17		L2ZZ	L2ZZ	L2ZZ	
B11		MCP	MCP	MCP	

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

 For More Information On This Product,  
 Go to: [www.freescale.com](http://www.freescale.com)

Table 4. Remaining Pins (continued)

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
D5		OVDD[00]	OVDD[00]	OVDD[00]	System bus I/O voltage.
D8		OVDD[01]	OVDD[01]	OVDD[01]	
D12		OVDD[02]	OVDD[02]	OVDD[02]	
E4		OVDD[03]	OVDD[03]	OVDD[03]	
E6		OVDD[04]	OVDD[04]	OVDD[04]	
E9		OVDD[05]	OVDD[05]	OVDD[05]	
E11		OVDD[06]	OVDD[06]	OVDD[06]	
F5		OVDD[07]	OVDD[07]	OVDD[07]	
H4		OVDD[08]	OVDD[08]	OVDD[08]	
J5		OVDD[09]	OVDD[09]	OVDD[09]	
L5		OVDD[10]	OVDD[10]	OVDD[10]	
M4		OVDD[11]	OVDD[11]	OVDD[11]	
P5		OVDD[12]	OVDD[12]	OVDD[12]	
R4		OVDD[13]	OVDD[13]	OVDD[13]	
R6		OVDD[14]	OVDD[14]	OVDD[14]	
R9		OVDD[15]	OVDD[15]	OVDD[15]	
R11		OVDD[16]	OVDD[16]	OVDD[16]	
T5		OVDD[17]	OVDD[17]	OVDD[17]	
T8		OVDD[18]	OVDD[18]	OVDD[18]	
T12		OVDD[19]	OVDD[19]	OVDD[19]	
B2	Input	$\overline{QACK}$	$\overline{QACK}$	$\overline{QACK}$	Pull up if unused <sup>1</sup>
J3	Output	$\overline{QREQ}$	$\overline{QREQ}$	$\overline{QREQ}$	
D3	Output	$\overline{RSRV}$	$\overline{RSRV}$	$\overline{RSRV}$	Put to test point useful for debug.
A12	Input	$\overline{SMI}$	$\overline{SMI}$	$\overline{SMI}$	Pull up if not driven constantly <sup>1</sup>
E10	Input	$\overline{SRESET}$	$\overline{SRESET}$	$\overline{SRESET}$	Pull up if not driven constantly <sup>1</sup>
H9	Input	SYSCLK	SYSCLK	SYSCLK	
F1	Input	$\overline{TA}$	$\overline{TA}$	$\overline{TA}$	Pull up <sup>1</sup>
A2	Input	TBEN	TBEN	TBEN	Pull up if not driven constantly <sup>1</sup>
A11	I/O	$\overline{TBST}$	$\overline{TBST}$	$\overline{TBST}$	Pull up <sup>1</sup>
B10	Input	TCK	TCK	TCK	
B7	Input	TDI	TDI	TDI	
D9	Output	TD0	TD0	TD0	
J1	Input	$\overline{TEA}$	$\overline{TEA}$	$\overline{TEA}$	Pull up <sup>1</sup>
C8	Input	TMS	TMS	TMS	Pull up

Common Footprint for the MPC750, MPC755, MPC7400, and MPC7410

 For More Information On This Product,  
 Go to: [www.freescale.com](http://www.freescale.com)



**Table 4. Remaining Pins (continued)**

Pin #	Type	MPC750	MPC755	MPC7400/ MPC7410 60x or MPX Bus	Comment
A10	Input	$\overline{\text{TRST}}$	$\overline{\text{TRST}}$	$\overline{\text{TRST}}$	Connect to $\overline{\text{HRESET}}$ directly if JTAG or COP not used or via logic.
K7	I/O	$\overline{\text{TS}}$	$\overline{\text{TS}}$	$\overline{\text{TS}}$	Pull up <sup>1</sup>
A9	Output	TSIZ[0]	TSIZ[0]	TSIZ[0]	
B9	Output	TSIZ[1]	TSIZ[1]	TSIZ[1]	
C9	Output	TSIZ[2]	TSIZ[2]	TSIZ[2]	
C10	I/O	TT[0]	TT[0]	TT[0]	Pull up <sup>1</sup>
D11	I/O	TT[1]	TT[1]	TT[1]	
B12	I/O	TT[2]	TT[2]	TT[2]	
C12	I/O	TT[3]	TT[3]	TT[3]	
F11	I/O	TT[4]	TT[4]	TT[4]	
C3	Output	$\overline{\text{WT}}$	$\overline{\text{WT}}$	$\overline{\text{WT}}$	
G8		VDD[00]	VDD[00]	VDD[00]	CPU core voltage
G10		VDD[01]	VDD[01]	VDD[01]	
G12		VDD[02]	VDD[02]	VDD[02]	
J8		VDD[03]	VDD[03]	VDD[03]	
J10		VDD[04]	VDD[04]	VDD[04]	
J12		VDD[05]	VDD[05]	VDD[05]	
L8		VDD[06]	VDD[06]	VDD[06]	
L10		VDD[07]	VDD[07]	VDD[07]	
L12		VDD[08]	VDD[08]	VDD[08]	
N8		VDD[09]	VDD[09]	VDD[09]	
N10		VDD[10]	VDD[10]	VDD[10]	
N12		VDD[11]	VDD[11]	VDD[11]	

<sup>1</sup> See the individual hardware specifications document for the recommended resistor value.

<sup>2</sup> See the individual hardware specifications document for more information.

### 1.3 Revision History

Table 5 shows this document's revision history.

**Table 5. Document Revision History**

Revision Number	Significant Changes
0, 0.1	Internal releases
1	Initial public release

#### How to Reach Us:

**Home Page:**

[www.freescale.com](http://www.freescale.com)

**E-mail:**

[support@freescale.com](mailto:support@freescale.com)

**USA/Europe or Locations Not Listed:**

Freescale Semiconductor  
 Technical Information Center, CH370  
 1300 N. Alma School Road  
 Chandler, Arizona 85224  
 +1-800-521-6274 or +1-480-768-2130  
[support@freescale.com](mailto:support@freescale.com)

**Europe, Middle East, and Africa:**

Freescale Halbleiter Deutschland GmbH  
 Technical Information Center  
 Schatzbogen 7  
 81829 Muenchen, Germany  
 +44 1296 380 456 (English)  
 +46 8 52200080 (English)  
 +49 89 92103 559 (German)  
 +33 1 69 35 48 48 (French)  
[support@freescale.com](mailto:support@freescale.com)

**Japan:**

Freescale Semiconductor Japan Ltd.  
 Headquarters  
 ARCO Tower 15F  
 1-8-1, Shimo-Meguro, Meguro-ku,  
 Tokyo 153-0064  
 Japan  
 0120 191014 or +81 3 5437 9125  
[support.japan@freescale.com](mailto:support.japan@freescale.com)

**Asia/Pacific:**

Freescale Semiconductor Hong Kong Ltd.  
 Technical Information Center  
 2 Dai King Street  
 Tai Po Industrial Estate  
 Tai Po, N.T., Hong Kong  
 +800 2666 8080  
[support.asia@freescale.com](mailto:support.asia@freescale.com)

**For Literature Requests Only:**

Freescale Semiconductor Literature Distribution Center  
 P.O. Box 5405  
 Denver, Colorado 80217  
 1-800-441-2447 or 303-675-2140  
 Fax: 303-675-2150  
[LDCForFreescaleSemiconductor@hibbertgroup.com](mailto:LDCForFreescaleSemiconductor@hibbertgroup.com)

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document. Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.



## How to Reach Us:

### Home Page:

[www.freescale.com](http://www.freescale.com)

### E-mail:

[support@freescale.com](mailto:support@freescale.com)

### USA/Europe or Locations Not Listed:

Freescale Semiconductor  
 Technical Information Center, CH370  
 1300 N. Alma School Road  
 Chandler, Arizona 85224  
 +1-800-521-6274 or +1-480-768-2130  
[support@freescale.com](mailto:support@freescale.com)

### Europe, Middle East, and Africa:

Freescale Halbleiter Deutschland GmbH  
 Technical Information Center  
 Schatzbogen 7  
 81829 Muenchen, Germany  
 +44 1296 380 456 (English)  
 +46 8 52200080 (English)  
 +49 89 92103 559 (German)  
 +33 1 69 35 48 48 (French)  
[support@freescale.com](mailto:support@freescale.com)

### Japan:

Freescale Semiconductor Japan Ltd.  
 Headquarters  
 ARCO Tower 15F  
 1-8-1, Shimo-Meguro, Meguro-ku,  
 Tokyo 153-0064  
 Japan  
 0120 191014 or +81 3 5437 9125  
[support.japan@freescale.com](mailto:support.japan@freescale.com)

### Asia/Pacific:

Freescale Semiconductor Hong Kong Ltd.  
 Technical Information Center  
 2 Dai King Street  
 Tai Po Industrial Estate  
 Tai Po, N.T., Hong Kong  
 +800 2666 8080  
[support.asia@freescale.com](mailto:support.asia@freescale.com)

### For Literature Requests Only:

Freescale Semiconductor Literature Distribution Center  
 P.O. Box 5405  
 Denver, Colorado 80217  
 1-800-441-2447 or 303-675-2140  
 Fax: 303-675-2150  
[LDCForFreescaleSemiconductor@hibbertgroup.com](mailto:LDCForFreescaleSemiconductor@hibbertgroup.com)

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document. Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

