

SENSOR PRODUCT SELECTOR GUIDE

Secure sensing solutions for automotive and industrial IoT



OVERVIEW

With successful experiences over 30 years and over 3 billion units shipped worldwide, NXP is a leader serving applications in the automotive, medical and industrial market spaces. NXP's Sensor solutions include a breadth of accelerometers, magneto-resistive and pressure solutions

covering different performances, sensing ranges and form factors. The portfolio is complemented with class leading development and enablement support spanning hardware tools, software tools and use case algorithms.

SELECTOR GUIDE SENSORS

MOTION SENSORS

Part Number	Description	Interface	Other	Package
High g Accelerometers				
FXLS90333	2-axis, XY, ± 50 to 500 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90433	2-axis, XZ, ± 50 to 500 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90230	1-axis, X, ± 50 to 500 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90130	1-axis, Z, ± 50 to 500 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93333	2-axis, $\pm XY$, 50 to 500 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93433	2-axis, XZ, ± 50 to 500 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93230	1-axis, X, ± 50 to 500 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90130	1-axis, Z, ± 50 to 500 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
Medium g Accelerometers				
FXLS90322	2-axis, XY, ± 15.5 to 150 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90422	2-axis, XZ, ± 15.5 to 150 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90220	1-axis, X, ± 15.5 to 150 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90120	1-axis, Z, ± 15.5 to 150 g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93322	2-axis, XY, ± 15.5 to 150 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93422	2-axis, XZ, ± 15.5 to 150 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93220	1-axis, X, ± 15.5 to 150g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS90120	1-axis, Z, ± 15.5 to 150 g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
Low g Accelerometers				
FXLS90421	2-axis, XZ, X axis ± 15.5 to 150g , Z axis ± 1.5 to 20g, 16-bit	SPI, DSI3	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS93421	2-axis, XZ, X axis ± 15.5 to 150g , Z axis ± 1.5 to 20g, 16-bit	PSI5	Auto grade 1 qual, -40 °C to 125 °C, ISO 26262:2018 ASIL B rating.	QFN 4 x 4 mm
FXLS8964AFR3	± 2 to 16 g, low-power 12-bit 3-axis accelerometer for automotive KeyFob application	I ² C, SPI	Auto qual, -40 °C to 105 °C	DFN 2 x 2x 0.95 mm
FXLS8967AFR3	± 2 to 16 g, low-power 12-bit 3-axis accelerometer for automotive security and convenience applications	I ² C, SPI	Auto qual, -40 °C to 105 °C	DFN 2 x 2 x 0.95 mm
FXLS8974CFR3	± 2 to 16 g, low-power 12-bit 3-axis accelerometer for use in a wide range of industrial and medical IoT applications.	I ² C, SPI	Industrial qual, -40 °C to 105 °C	DFN 2 x 2x 0.95 mm
FXLS8971CFR3	± 2 to 16 g, high performance 12-bit 3-axis accelerometer for Industrial/IoT applications that require excellent offset and sensitivity stability over temperature	I ² C, SPI	Industrial qual, -40 °C to 105 °C	QFN 12-pin, 3 x 3 x 1.25 mm
FXLS8961AFR3	± 2 to 16 g, high performance 12-bit 3-axis accelerometer for automotive security and convenience applications that require excellent offset and sensitivity stability over temperature	I ² C, SPI	Industrial qual, -40 °C to 105 °C	QFN 12-pin, 3 x 3 x 1.25 mm

PRESSURE SENSORS

Part Number	Description	Interface	Other	Package
Barometric Pressure Sensors				
FXPQ3115BV	20-115 kPa, 1.5 kPa or 25 cm resolution	I ² C	Biomedical Pressure Sensor, -40 °C to 85 °C operating temperature	LGA 3 x 5mm
MPL3115A2	20-115 kPa, 1.5 kPa or 25 cm resolution	I ² C	2 interrupts on pressure, altitude, temperature, -40 °C to 85 °C operating temperature	LGA 3 x 5mm
MPL3150A2	50-150 kPa, 1.5 kPa or 25 cm resolution	I ² C	2 interrupts on pressure, altitude, temperature, -40 °C to 85 °C operating temperature	LGA 3 x 5mm

PRESSURE SENSORS (CONT.)

Absolute Pressure Sensors				
FXPS7115DS4T1	40 kPa to 115 kPa	SPI	4.67 % accuracy over entire temperature range and life, Media resistant gel, -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7115DI4T1	40 kPa to 115 kPa	I ² C	4.67 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7165DS4T1	60 kPa to 165 kPa	SPI	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7165DI4T1	60 kPa to 165 kPa	I ² C	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7250DS4T1	20 kPa to 250 kPa	SPI	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7250DI4T1	20 kPa to 250 kPa	I ² C	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7400DS4T1	20 kPa to 400 kPa	SPI	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7400DI4T1	20 kPa to 400 kPa	I ² C	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7550DS4T1	20 kPa to 550 kPa	SPI	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7550DI4T1	20 kPa to 550 kPa	I ² C	2 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7250A4T1	20 kPa to 250 kPa	Analog	3 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7400A4T1	20 kPa to 400 kPa	Analog	3 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
FXPS7550A4T1	20 kPa to 550 kPa	Analog	3 % accuracy over entire temperature range and life, Media resistant gel -40 °C to 125 °C operating temperature	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
Battery Pressure Monitoring				
NBP8FD4T1	40 kPa to 250 kPa	SPI	Absolute FIFO, relative and rate-of-change detections, host wake-up, auto qual	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
NBP9FD4T1	40 kPa to 250 kPa	SPI, PWM	Absolute FIFO, relative and rate-of-change detections, host wake-up, auto qual	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)
Vacuum Pressure Sensors				
MP3V5050	-50 kPa to 0 kPa	Analog 0.06 V to 2.82 V	2 % accuracy	SOP ported, SOP dual port
MPXHV6115V	-115 kPa to 0 kPa	Analog 0.2 V to 4.6 V output	1.5 % accuracy, auto qual	SOP and SOP ported
MPXV5050VC6U	-50 kPa to 0 kPa	Analog 0.1 V to 4.6 V	2.5 % accuracy	SOP ported
MPXV7002	-2 kPa to 2 kPa	Analog 0.5 V to 4.5 V	2.5 % accuracy	SOP ported and dual port
MPXV7007	-7 kPa to 7 kPa	Analog 0.5 V to 4.5 V	5 % accuracy	SOP ported, SOP dual port
MPXV7025	-25 kPa to 25 kPa	Analog 0.2 V to 4.7 V	5 % accuracy	SOP ported, SOP dual port
Differential/Gauge Pressure Sensors < 10 kPa				
MPVZ5050	0 kPa to 50 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy, media resistant gel	SOP ported
MPXx2053	0 kPa to 50 kPa	Analog 40 mV	Compensated and calibrated	x=V SOP and ported SOP, x=M MPAK
MPXx2102	0 kPa to 100 kPa	Analog 40 mV	Compensated and calibrated	x=V SOP and ported SOP, x=M MPAK
MPX2300DT1	0 kPa to 40 kPa	Analog	Disposable bio compatible system	ChipPak package
MPXM2051G	0 kPa to 50 kPa	Analog 40 mV	Compensated and calibrated	MPAK
MPXV5050	0 kPa to 50 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy	SOP ported and dual port
MPXV5100	0 kPa to 100 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy	SOP ported and dual port
MPXV5010	0 kPa to 10 kPa	Analog 0.2 V to 4.7 V	5 % accuracy	SOP, SOP dual port, SOP ported

PRESSURE SENSORS (CONT.)

Part Number	Description	Interface	Other	Package
Differential/Gauge Pressure Sensors up to 115 kPa				
MPVZ5050	0 kPa to 50 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy, media resistant gel	SOP ported
MPXx2053	0 kPa to 50 kPa	Analog 40 mV	Compensated and calibrated	x=V SOP and ported SOP, x=M MPAK
MPXx2102	0 kPa to 100 kPa	Analog 40 mV	Compensated and calibrated	x=V SOP and ported SOP, x=M MPAK
MPX2300DT1	0 kPa to 40 kPa	Analog	Disposable bio compatible system	ChipPak package
MPXM2051G	0 kPa to 50 kPa	Analog 40 mV	Compensated and calibrated	MPAK
MPXV5050	0 kPa to 50 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy	SOP ported and dual port
MPXV5100	0 kPa to 100 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy	SOP ported and dual port
Differential/Gauge Pressure Sensors up to 1000 kPa				
MPXx2202	0 kPa to 200 kPa	Analog 40 mV	Compensated	x=V SOP and ported SOP, x=M MPAK
MPX5500	0 kPa to 500 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy	Unibody packages
MPX5700	0 kPa to 700 kPa	Analog 0.2 V to 4.7 V	2.5 % accuracy	Unibody packages
MPX5999	0 kPa to 1000 kPa	Analog 0.2 V to 4.7 V		Unibody packages
Wireless Sensor / Tire Pressure Monitoring				
FXTH87xx	100 kPa to 1800 kPa	GPIO, RF, LF	Single- or dual-axis accelerometers, SO8 CPU with 16 kB flash, 512 B RAM, 315/434 MHz transceiver, 125 kHz LF receiver, temperature and voltage monitoring, auto grade 1 qualification	7 x 7 x 2.2 mm QFN-FAM (Wettable Flanks)
NTM88xxx5	100 kPa to 1100 kPa	GPIO, RF, LF	Single- or dual-axis accelerometers, SO8 CPU with 16 kB flash, 512 B RAM, 315/434 MHz transceiver, 125 kHz LF receiver, temperature and voltage monitoring, auto grade 1 qualification	4 x 4 x 1.98 mm QFN-FAM (Wettable Flanks)

MAGNETIC SENSORS

Part Number	Description	Interface	Other	Package
Magnetic Switch				
NMH1000	-210 G to 210 G	I ² C or stand alone	Magnetic switch ultra low power voltage down to 1.2 V and ultra low power down to 75 nA	DFN 1.4 x 1.4 x 0.85 mm
Programmable Angle Sensors				
KMA310/A	Automotive programmable angle sensor	Single channel, analog/SENT output	Angle range 180°, max operating temperature 180°C	SOT1288-3 (SIL3)
KMA320/A	Automotive programmable angle sensor	Dual channel, analog/SENT output	Angle range 180°, max operating temperature 180°C	SOT1188-2 (SIL4)
KMA321/A	Automotive programmable angle sensor	Single channel, analog/SENT output	Angle range 180°, max operating temperature 180°C	SOT1188-2 (SIL4)
KMZ80	General purpose programmable angle sensor	Single channel, analog/SENT output	Angle range 180°, max operating temperature 150°C	SOT96-1
Angle Sensors with Integrated Amplifier				
KMZ60/A	Angle sensor with integrated amplifier	amplified sine / cosine; 0.07.... 0.93 V _{cc}	Angle range 180° max operating temperature 150°C	S08; SOT96-1

Follow us on social media at



www.twitter.com/NXP_Auto



www.facebook.com/nxpsemi



<https://www.linkedin.com/company/nxp-semiconductors>

www.nxp.com/sensors

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. All rights reserved.
© 2014–2023 NXP B.V.

Document order number: SENSSELECT REV 12